

## 2-SPEED ROTARY DRILL

### B 13/2 RLE



#### B 13/2 RLE applications

- Small and large drill holes (1st/2nd gear)
- Installing screws, also large screws
- Mixing and stirring viscous substances
- Working with hole saws
- Removing paint and rust with a brush
- Polishing

#### B 13/2 RLE features

- High torque in 1st gear (45 Nm)
- High speed in 2nd gear
- Speed infinitely adjustable with pushbutton switch/adjusting dial
- Clockwise/anticlockwise selector switch
- High-strength magnesium gear housing
- Robust heavy-duty drill spindle mounting
- 3-level reduced 2-speed gear
- High quality keyless chuck for a rapid and easy tool change

TECHNICAL DATA		B 13/2 RLE
Rated power		650 W
Screws up to		dia. 12 mm
Set torque (1st gear)		45 Nm
Machine weight		1.9 kg
Drill spindle thread		1/2" - 20 UNF
Spindle collar dia.		43 mm
Chuck clamping range		dia. 1.5 - 13 mm
Drilling dia. in	<b>1st gear</b>	<b>2nd gear</b>
steel	16 mm	8 mm
softwood	40 mm	20 mm
lightweight materials with hole saw	105 mm	50 mm
Rated speed	0 - 450 rpm	0 - 1550 rpm

#### Order-No. B 13/2 RLE

Standard specification: DUSS B 13/2 RLE 2-speed rotary drill, keyless chuck with locking screw, side handle, depth stop.