

## COMBI HAMMER

### P 30



#### P 30 applications

- Drilling anchor holes, fastening cladding panels
- Overhead work and drilling rows of holes
- Sinking sockets
- Chasing grooves and slots
- Removing plaster and tiles
- Cleaning up surfaces
- Precision repair work

#### P 30 features

- Electronic for constant speed control
- Speed and impact force infinitely adjustable with pushbutton switch/adjusting dial
- Rapid changeover from hammer drilling to chiselling and vice versa
- Chisel can be positioned in twenty ways
- Vibration damping elements
- Maintenance-free (with lifetime lubrication)
- Rapid tool change
- Low-wear safety clutch

TECHNICAL DATA	P 30
Rated power	710 W
Drilling range with drill bit	dia. 5 - 35 mm
Drilling range with core bit	dia. 45 - 82 mm
Drilling performance* (dia. 22 mm)	180 mm/min
Chiselling performance* with pointed chisel	approx. 80 kg/h
Single impact energy	0 - 5.7 J
Rated speed	0 - 390 rpm
Impact rate, adjustable	0 - 3000 impacts/min
Machine weight	4.5 kg
Chuck	13 mm hexagon

\* In hard C45/55 concrete

#### Order-No. P 30

Standard specification: Duss P 30 combi hammer, side handle, tube of grease, dust cup, carrying case for machine and tools.