

DEMOLITION HAMMER

PK 300 A



PK 300 A applications

- Demolition work
- Producing breaches and openings
- Cleaning up surfaces
- Renovation of floors, breaking up floors and creating large channels in floors

PK 300 A features

- Replaces a pneumatic breaker in many cases
- Very high demolition performance, light weight and balanced weight distribution
- Trigger lock for continuous operation, ensuring non-fatiguing work
- Perfectly harmonised percussion mechanism for precise work and highest reliability
- Active vibration damping (RVA), ensuring comfortable continuous use
- Screw-in, vibration damped auxiliary handle for non-fatiguing, back-saving posture when chiselling downwards
- Vibration damped D-handle
- LED display for optimum service planning
- Compact, robust design with aluminium and magnesium housings
- Automatic chuck with integral no-load impact damping
- Dust guard for prolonged service life
- Electronic for constant impact rate control
- Impact rate and impact force infinitely adjustable with adjusting dial
- Robust, 22 mm hexagon chuck for extra-long service life
- Maintenance-free (with lifetime lubrication)



TECHNICAL DATA	PK 300 A
Rated power	1700 W
Chiselling performance* with pointed chisel	approx. 730 kg/h
Single impact energy	14 - 27 J
Impact rate, adjustable	1000 - 1900 impacts/min
Machine weight	13.6 kg
Chuck	22 mm hexagon
Vibration data	chiselling
Normal setting	9.1 m/s ²
Compressor setting	9.6 m/s ²

* In hard C45/55 concrete



Order-No. PK 300 A

Standard specification: Duss PK 300 A demolition hammer, D-handle, auxiliary handle, tube of grease, carrying case for machine and tools.