

## BREAKER

### PKX 7



#### PKX 7 applications

- Removing plaster and tiles
- Chasing grooves and slots
- Chiselling work
- Cleaning up surfaces
- Producing breaches and openings
- Precision repair work

#### PKX 7 features

- Active vibration damping (RVA), ensuring comfortable continuous use
- Screw-in, vibration damped auxiliary handle for non-fatiguing, back-saving posture when chiselling downwards
- Vibration damped D-handle
- LED display for optimum service planning
- Consistently high engine output thanks to optimised engine cooling
- Pneumatic impact mechanism designed for optimum efficiency
- Trigger lock, ensuring non-fatiguing work
- Electronic for constant impact rate control
- Impact rate and impact force infinitely adjustable with adjusting dial
- Chisel can be positioned in twenty ways
- Maintenance-free (with lifetime lubrication)



TECHNICAL DATA	PKX 7
Rated power	1150 W
Chiselling performance* with pointed chisel	approx. 280 kg/h
Single impact energy	5 - 10.5 J
Impact rate, adjustable	1500 - 2900 impacts/min
Machine weight	7.3 kg
Chuck	SDS-max
Vibration data	chiselling
Normal setting	6.7 m/s <sup>2</sup>
Compressor setting	4.7 m/s <sup>2</sup>

\* In hard C45/55 concrete

#### Order-No. PKX 7

Standard specification: Duss PKX 7 breaker, D-handle, auxiliary handle, tube of grease, carrying case for machine and tools.