

## 2-SPEED IMPACT DRILL

### SB 13/2 RLE



#### SB 13/2 RLE applications

- Drilling in masonry and concrete
- Drilling anchor holes
- Small and large drill holes (1st/2nd gear)
- Installing screws, also large screws
- Mixing and stirring viscous substances
- Working with hole saws
- Sinking sockets with core bits
- Removing paint and rust with a brush
- Polishing

#### SB 13/2 RLE features

- Rapid changeover, drilling/percussion drilling
- High torque in 1st gear (45 Nm)
- High speed in 2nd gear
- Speed and impact force infinitely adjustable with pushbutton switch/adjusting dial
- Clockwise/anticlockwise selector switch
- High-strength magnesium gear housing
- Robust heavy-duty drill spindle mounting
- 3-level reduced 2-speed gear
- High quality keyless chuck for a rapid and easy tool change

TECHNICAL DATA		SB 13/2 RLE	
Rated power	650 W		
Screws up to	dia. 12 mm		
Set torque (1st gear)	45 Nm		
Machine weight	2.0 kg		
Drill spindle thread	1/2" - 20 UNF		
Spindle collar dia.	43 mm		
Max. impact rate	42000 impacts/min		
Chuck clamping range	dia. 1.5 - 13 mm		
Drilling dia. in	<b>1st gear</b>	<b>2nd gear</b>	
steel	16 mm	8 mm	
softwood	40 mm	20 mm	
stone	20 mm	13 mm	
lightweight materials with hole saw	105 mm	50 mm	
sand-lime brick and masonry with core bit	66 mm	-	
Rated speed	0 - 450 rpm	0 - 1550 rpm	

#### Order-No. SB 13/2 RLE

Standard specification: DUSS SB 13/2 RLE 2-speed impact drill, keyless chuck with locking screw, side handle, depth stop.